

HIGH DEFINITION 4 IN 1 FIXED DOME CAMERA

VV-AC2M56D-M13F3IRA13/V4
2.4 MP IR NIGHT VISION FULL HD CAMERA



FEATURES

- 2.4 Megapixel HD1080P Resolution
- 4 in 1 (AHD/TVI/CVI/CVBS) Camera Supported
- 1/2.7" Progressive Scan Sensor
- OSD Menu supported through UTC
- High performance Smart IR LEDs with intensity control
- Inbuilt IR LEDs for 20 mtr IR range
- 3.6 mm IR corrected Lens
- Premium Internal Dome Enclosure



1/2.7" Progressive Scan Sensor

3D DNR

Mechanical ICR

Smart Array IR

Auto White Balance

VV-AC2M56D-M13F3IRA13/V4

Camera	Image sensor	1/2.7" Progressive Scan Sensor
	Signal System	PAL/NTSC
	Frequency	50 Hz (PAL) / 60 Hz (NTSC)
	Horizontal Resolution	2.4 Megapixel
	Minimum Illumination	Color : 0.01Lux @ F1.2, 0.015 lux @ F1.4 B&W: 0 Lux at IR on
	Signal to Noise	> 50 dB
	Shutter Time	1/50s ~ 1/100,000s
	Gain Control	Auto
	White Balance	Auto
	DNR	Inbuilt 3D DNR (Digital Noise Reduction) circuit
	Field of View (FOV)	85°
	Frame	PAL:25fps/NTSC:30fps
Lens	Lens Type	3.6mm IR corrected lens
	Lens Mount	M14
	Focus	Fixed
Day/Night Functionality	Day & Night	True Day & Night with ICR
	IR Cut	High performance Mechanical IR Cut Filter with auto switch
	IR Source	High performance 18 no. Smart IR LEDs, 850nm wave length
	IR Range	Up to 20 Mtrs
Operational Features	Wide Dynamic Range (WDR)	Digital WDR
	Backlight compensation	Supported
	OSD	Supported through UTC
Interface	Video Output	1 x BNC (AHD / TVI / CVI/CVBS)
	Power Input	Standard DC Jack
Electrical	Power Requirement	DC 12V (± 10%)
	Power Consumption	Max 5 W with IR on
Environmental	Enclosure	IP66 Weather proof Indoor Dome Enclosure
	Operating Temperature	-10°C to + 55°C
	Operating Humidity	90% or less (non-condensing)
Mechanical	Color	White
	Dimensions	Φ93mm(base)X Φ52mm(front)X77mm(height)
	Weight	146g
Certifications	Certifications	CE, FCC, RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

